

TREE TIPS




Technical Notes

CREATING RANDOM POINT SAMPLES IN POLYGONS FOR PRISM CRUISING


ArcGIS 9

ISOLATING AND BUFFERING POLYGONS

1. Run a selection query to focus on desired polygons.
2. Open ArcToolbox. Double click "Analysis Tools", then "Proximity", and lastly "Buffer" which will open the Buffer Wizard.
3. Set the input shapefile, the one with the selected features, and the buffer distance (Positive numbers for an exterior buffer, negative numbers for an interior buffer). Also set the correct units for the buffer distance.
 - Although there is no spot to tell the wizard to use the selected features, the buffer wizard will only buffer the selected features.



Step 1



Step 2

TREE TIPS

GENERATING RANDOM POINTS


- Open the Attribute Table
- By looking at the HA field, select the polygons that fall within the classes outlined in Table 1. Select only the polygons that fall within one single class.
 - To select polygons in the Attribute table, left click in the left margin beside the record.
- Open the Hawth's Tools menu, move the mouse pointer to "Sampling Tools", then left click on "Generate Random Points".
- Set the input layer to the buffer shapefile created, check the "Use Selected Features Only" box, check the "Prevent Points..." box and set to the water shapefile so that no points are generated in the water. Next, check the "Enforce Minimum Distance..." box to set the threshold for how close the generated points can be. After that, select the "Generate this number of points per polygon" button and set the "Polygon Unique Id field" to the field containing the stand number and set the "...number of points per polygon" to the class chosen from Table 1. Lastly, set the path to the desired location for the new point shapefile and set the name of the new point shapefile.

Table 1: Stand Sample Parametres

Stand Size	# of Plots	Station Spacing
<10 ha	10	20
10-20 ha	20	20
>20 ha	20	40

FLAG	XLABEL	YLABEL	CLASS	MS_1	WHHD	MU	WCS	STANDNO	HA	YRO	OWN	TOWNSHIP
678353.625		5041084.886	NZ	176755040	PH	451	0	588	9.06	1816	7	PECK
678275.313		5040329.688	NZ	176755040	PH	451	0	588	15.5	1796	7	PECK
677504.313		5040035.633	NZ	176755035	GH	451	0	588	8.88	1816	7	PECK
680584.719		5038594.105	NZ	176805035	GH	451	0	578	15.55	1851	7	PECK
678935.687		5039106.197	NZ	176755035	GH	451	0	578	18.2	1841	7	PECK
679109.251		5038541.887	NZ	176755035	GH	451	0	578	11.76	1841	7	PECK
681718.72		5038142.263	NZ	176805035	GH	451	0	578	7.75	1858	7	PECK
678446.281		5037642.663	NZ	176755035	GH	451	0	578	13.95	1846	7	PECK
677577.562		5038816.513	NZ	176755035	GH	451	0	587	18.87	1846	7	PECK
676381.438		5036293.422	NZ	176755035	GH	451	0	588	30.79	1836	7	PECK

Step 5



Step 6


Hawths Tools

www.spatialecology.ca

DNR Garmin

www.dnr.state.mn.us/mis/gis/tools/arcview/extensions/DNRGarmin/DNRGarmin.html

or search DNR Garmin



Step 7

TREE TIPS


CREATING UNIQUE ID NUMBERS

8. Open the Attribute table for the Random Sample point shapefile that was just created.
9. Click on the "Options" menu in the lower left portion of the window and "Add Field".
10. Create a Short Integer field named UniqueID
11. Select all the points with the same stand number.
12. Right Click on the UniqueID title and select calculate
13. Load the sequential ID.cal then press OK*
14. Follow Steps 1 through 4 to create a unique ID for the points within each selected stand.
15. Add a text Field with a length of 25 characters and call it "Ident"
16. Calculate the values for this field, uncheck "Advanced" to clear the other formula and input this formula:


[STANDNO] & "_" & [UniqueID]

ADDING POINTS TO YOUR GARMIN GPS


17. Plug your Garmin GPS into your computer
18. Open DNR Garmin
19. Click the File Menu, move the mouse pointer over "Load From", then "File" and finally choose the Random Points shapefile.
20. Click the Waypoint Menu and then click "Upload" The waypoints should now be in your GPS unit with the records in the "Ident" field as the name.




Step 11



Step 11



Step 17



Step 20

Publication Produced and Written By:
Paul Courville, October 2006.

* Sequential ID formula:

```
Static rec As Long
Dim pStart As Long
Dim pInterval As Long
```

```
' adjust start value if you want it to
' start at a value other than 1.
```

```
' For example, 1000.
```

```
' =====
pStart = 1
```

```
' adjust interval value if you want it to
' start at a value other than 1.
```

```
' For example, 2.
```

```
' =====
pInterval = 1
```

```
If (rec = 0) Then
```

```
rec = pStart
```

```
Else
```

```
rec = rec + pInterval
```

```
End If
```

```
__esri_field_calculator_splitter__
```

```
rec
```